

# RCF27 SERIES SINGLE SPINDLE ROTARY CUTTERS

HP REQUIRED  
35-130 HP

CUTTING CAPACITY  
3"

HITCH  
Cat. 1, 2 & 3



CUTTERS

## Roundback with a Smooth Top.

The RCF27 Series Rotary Cutter is a smooth top version of our RCR26 Series, offering the same great cut and is ideal for grass, weeds, crops, brush, and small trees up to 3 inches in diameter. These units come equipped standard with a 3/16" thick heavy-duty stump jumper and replaceable bolt-on skid shoes.

**5 YEAR**  
LIMITED GEARBOX  
WARRANTY

- Smooth top design
- All welded deck
- Clevis style lower hitch
- Floating top hitch
- 84" Pull-type model available
- Dual wheels optional on 3-Point 84" model, Standard on Pull-Type



Replaceable bolt-on skid shoes provide sidewall reinforcement and protection to the bottom of sidewall.



Optional shields are available for the front and rear to protect against flying debris.



The laminated tailwheel is long lasting in rough conditions and 1-1/2" heavy-duty spindle protects the assembly.

	RCF2760	RCF2772	RCF2784
<b>Horsepower</b>	35-130 HP		60-130 HP
<b>Hitch</b>	Cat. 1 & 2		Cat. 2 & 3, Pull-Type
<b>Working Width</b>	60" (152)	72 (183)	84 (213)
<b>Overall Width</b>	67"	79"	89"
<b>Overall Length</b>	109"	121-3/4"	Single 132.5", Dual 130"
<b>Weight - lb (kg)</b>	955 (433)	1,072 (486)	1,354 (614), Pull-Type: 1632 (740)
<b>Cutting Height</b>	1-1/2" - 12"		
<b>Cutting Capacity</b>	3" Diameter		
<b>Deck</b>	All Welded, Smooth Top		
<b>Deck Thickness</b>	10 Gauge		
<b>Deck Height</b>	11-1/4"	10-1/8"	
<b>Side Thickness</b>	1/4"		
<b>Safety Guards</b>	Front: Chain or Rubber, Rear: Chain		
<b>Skids</b>	Replaceable		
<b>Blades</b>	Free Swinging High Suction, 1/2" x 4" - Heat Treated		
<b>Blade Bolt</b>	Keyed with Hardened, Flat Washer & Lock Nut		
<b>Blade Tip Speed</b>	12,384 fpm	14,861 fpm	14,369 fpm
<b>Dishpan</b>	3/16" x 24" Round, Dish Shaped	3/16" x 30-1/2" Round, Dish Shaped	3/16" x 24" x 38" Oval, Dish Shaped
<b>Gearbox Rating<sup>^</sup></b>	130 HP		
<b>Gearbox</b>	540 RPM 1-3/8" - 6 Spline		
<b>Gearbox Output Shaft</b>	2"		
<b>Driveline</b>	Cat. 4 with 4 Plate Slip-Clutch		
<b>Tailwheel(s)</b>	15" Laminated, w/Cast Iron Hub, Tapered Roller Bearings		
<b>Colors</b>			



<sup>\*</sup>See dealer for complete warranty information. <sup>^</sup>Based on field performance.