

RCF20 SERIES SINGLE SPINDLE ROTARY CUTTERS

HP REQUIRED
20-90 HP

CUTTING CAPACITY
2"

HITCH
Cat. 1 & 2



CUTTERS

The ideal cutter for rural grass maintenance - in a smooth top design.

- Smooth top for easier cleaning
- ASABE Category 3 driveline
- Fully-welded deck
- Available rubber or chain guards - front and rear
- High blade tip speed
- 84" Features single or dual tailwheel option



5 YEAR
LIMITED GEARBOX
WARRANTY*



Cast floating top link follows ground undulations.



10 Gauge stump jumper with 1" thick blade bar slides over stumps, rocks and debris.



Extended cutter front allows for increased material flow and added protection.

	RCF2060	RCF2072	RCF2084
Horsepower	20-65 HP		45-90 HP
Hitch	Cat. 1 - Floating Top Link, Clevis Type Lower Links, QH Adaptable		Cat. 1 & 2 Floating Top Link, Clevis Type Lower Links, QH Adaptable
Working Width (cm)	60 (152)	72 (183)	84 (213)
Overall Width	65"	77"	89"
Overall Length	98"	109-1/2"	Single: 133"; Dual 126"
Weight - lb (kg)	620 (281)	745 (338)	Sgl Tailwheel: 1,047 (475) Dual Tailwheel: 1,155 (524)
Cutting Height	1-1/2" - 12"		
Cutting Capacity	2" Diameter		
Deck Thickness	10 Gauge		
Deck Height	9-11/16"	11"	11-15/16"
Safety Guards	Rear Metal Banding - Standard		
Optional Guarding	Front: Rubber or Chain; Rear: Rubber or Chain		
Skids	Weld-on (Bolt on Accessory Skid Shoes Available)		
Blades	2 ea. (1/2" x 3" Heat Treated) Free Swinging High-Lift		2 ea. (1/2" x 4" Heat Treated) Free Swinging High-Lift
Blade Tip Speed	16,363 fpm	14,955 fpm	17,113 fpm
Dishpan	Round, 10 Ga. x 24" Dia, Dish Shaped		Oval, 3/16" x 27"
Gearbox Rating[^]	65 HP		130 HP
Gearbox	540 RPM, Beveled Gears, Cast Iron Housing		
Driveline	Cat. 3; Shear Bolt or 2-Plate Slip-Clutch		Cat. 4; 2-Plate Slip-Clutch
Tailwheels	4" x 15" Laminated Tire or 4" x 16" Molded Rubber - 360 Degree Swivel		Single or Dual 4" x 15" Laminated Tire w/ Cast Iron Hub - 360 Degree Swivel
Colors			



*See dealer for complete warranty information. [^]Based on field performance.